

ST[®] Clip Screw Metal to Metal

Features and Benefits

- A self-drilling Pancake Head is available to attach standing seam roof clips to steel framing.
- Low profile head design provides excellent pull over strength.
- Ruspert[®] corrosion resistant coating is standard on all Clip Screws.

SIZE	HEAD STYLE	CARTON QTY.	WEIGHT/M
10 x 1" SD CARBON STL.	#2 SQUARE/PHILLIPS COMBO	3000	7.0
10 x 1-1/2" SD CARBON STL.	#2 SQUARE/PHILLIPS COMBO	2500	9.0



SUBSTRATE	PULL OVER STRENGTH LBS. ULT.	
	PENETRATION	VALUE
HRS Primed Only	16	830
HRS Primed Only	14	1006
HRS Primed Only	12	1495
G-90 GALVANIZED	18	731

SUBSTRATE	PULL OVER STRENGTH LBS. ULT.		
	GAUGE	THICKNESS	VALUE
AZ55 Galvalume	29	.015	529
AZ55 Galvalume	26	.019	779
AZ55 Galvalume	24	.024	1128
AZ55 Galvalume	22	.032	1512

POINT DIAMETER	.151/.156
MAJOR DIAMETER	.189/.183
MINOR DIAMETER	.135/.141
HEAD DIAMETER	.443/.423
ULT. TENSILE STRENGTH	1920 LBS.
MIN. TORSIONAL STRENGTH	61 IN-LBS.
NOM. SHEAR STRENGTH	1633 LBS.

Applications

