



Product Highlights

FelTex, is our premium synthetic roof underlayment and is among the safest, strongest, and best-performing on the market. It balances strength and weight, provides dynamic steep-slope traction, and will not buckle, warp or crack. FelTex is rated for commercial and residential applications using roofing nails (3/8-inch head), and is an ideal underlayment for asphalt, shingles, metal, tile, slate, and a variety of sloped roofing materials. Two skid-resistant surfaces include the proprietary Fiber Claw® top and a deck grabbing rubberized bottom. These surfaces along with unmatched strength and durability make FelTex an ideal steep slope underlayment choice. Whether you're working on a FelTex-protected roof or living underneath one, you'll appreciate FelTex's quality.

Features

- Safest: Skid-resistant polymer coating underneath and proprietary Fiber Claw™ walking surface offers dynamic steep slope traction.
- Hail Rated: FelTex has a Class 4 hail rating (UL 2218) and may help reduce insurance costs.
- Strongest: FelTex is designed for high traffic and high winds with the most strength and durability available.
- Lighter: FelTex is lighter than #15 or #30 felt and easier to handle during all stages of installation.
- Simpler to Apply: FelTex installs quickly and easily. It is lighter, stronger, and covers more area than traditional underlayments.
- More Coverage: FelTex offers five times more coverage per roll than Type 30 felt.
- Gray Color: Provides a comfortable working surface in all temperatures
- Won't Buckle, Warp or Crack: Superior lay-flat properties and water resistance keeps FelTex from warping, wrinkling, and cracking in cold weather.
- UV Exposure Rating: FelTex is treated to resist excessive degradation from normal UV exposure for up to six months. See installation guidelines for details.
- Asphalt Free: FelTex is 100% inorganic and will not rot or mold.
- Sustainable: FelTex is environmentally responsible and may contribute to your LEED and NGBF ratings.
- Warranty: Limited Lifetime Warranty.
- Roll Size: 48" x 250'

SystemComponents
Corporation

Product Specifications

Property	Test Method	Typical Property
Tensile Strength (MD/CD)	ASTM D 882	MD 126/CD 92
Tear Resistance	ASTM D 4533	MD 41/CD 37
Rupture Resistance	ASTM D 3462-02 (LBF)	87
Beach Puncture	ICC AC-08	Pass
Long Term Sag	ICC AC-08	Pass
Liquid Water Transmission	ASTM D 4869-02	Pass
Ultra Violet Aging	ICC-ES AC 188	Pass
Accelerated Aging	ICC-ES AC 188	Pass

*Results reflect typical properties of control/non-conditional specimen. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.

