

Universal Master Flash®

Features and Benefits

- Manufactured from EPDM or silicone rubber, Universal Master Flash® is compounded for maximum resistance to ozone, UV light, & temperature extremes.
- Flexible aluminum base will allow the flashing to conform to any metal roof configuration. Pipe location can be centered in the flat of the panel or the rib. Urethane sealant & self-drilling screws complete the installation
- Universal Master Flash® are well marked so they can easily be cut with shears to fit exactly the pipe size used.
- Universal Master Flash® are available in Black or Gray EPDM as well as Red or Gray high temperature Silicone.



PIPE SIZE	BASE DIAMETER	COLOR MATERIAL
MINI Closed - 1" (0 - 25mm)	4" (101mm)	Available EPDM Colors: Brown, Black, Gray, White, Dark Green, Light Green, Dark Blue, Light Blue, Bright Red, and Terra Cotta
#1 Closed - 1-7/8" (0 - 47mm)	4.75" (120mm)	
#2 1-1/4" - 3" (44 - 76mm)	6-1/4" (159mm)	Silicone: Red and Grey
#3 Closed - 5" (0 - 127mm)	7-3/4" (196mm)	
#4 2-1/4" - 6-1/4" (57 - 158mm)	9-1/4" (234mm)	
#5 3-1/2" - 7-3/4" (88 - 196mm)	10-1/2" (266mm)	
#6 5" - 9" (127 - 228mm)	12-1/2" (317mm)	
#7 5-1/2" - 11" (139 - 279mm)	14-1/2" (368mm)	
#8 6" - 13" (152 - 330mm)	16-1/2" (412mm)	
#9 7-3/4" - 19" (196 - 482mm)	25-1/4" (641mm)	

	EPDM 500	SILICONE
Advanced Ozone Resistance Tested to...	70 hr @500 pphm	70 hr @ 500 pphm
High Temperature Resistance Tested to...		
Intermittent	+135°C (+275°F)	+260°C (+500°F)
Continuous	+100°C (+212°F)	+225°C (+500°F)
Low Temperature Resistance Tested to...	-55°C (-65°F)	-74°C (-100°F)
Tensile Set Maximum...	10MPa (1450psi)	5MPa (700psi)
Compression Set Maximum...	25%	50%

EASY INSTALLATION



1. Choose pipe opening and trim



2. Slide over pipe



3. Form to roof profile



4. Apply sealant



5. Fasten to complete