

Fix-A-Flash Master Flash®

Features and Benefits

- Designed for an over-sized hole, but smaller diameter pipe, over which a standard Fix-A-Flash Master Flash™ will not fit.
- Manufactured from EPDM or silicone rubber, the FIX-A-FLASHTM material compound is designed for maximum resistance to ozone, UV light, & temperature extremes.
- Each FIX-A-FLASH is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- FIX-A-FLASH have a flexible aluminum band that will conform to any metal roof configuration.



PIPE SIZE	BASE DIAMETER	COLOR MATERIAL
6-3/4" - 15-1/2" (171-393mm)	19-1/2" (495mm)	Black/Gray EPDM Red Silicone
0" - 15-1/2" (0-393mm)	19-1/2" (495mm)	Black/Gray EPDM Red Silicone



		EPDM 500	SILICONE
Advanced Ozone Resistance	e Tested to	70 hr @500 pphm	70 hr @ 500 pphm
High Temperature Resistance	e Tested to Intermittent Continuous	+135°C (+275°F) +100°C (+212°F)	+260°C (+500°F) +225°C (+500°F)
Low Temperature Resistanc	e Tested to	-55°C (-65°F)	-74°C (-100°F)
Tensile Set Maximum Compression Set Maximum		10MPa (1450psi) 25%	5MPa (700psi) 50%

