



Product Highlights

Ultra HT Wind & Water Seal™ is a self-adhering waterproofing underlayment composed of a white, non-slip cross-laminated polymer film, laminated to a high temperature rubberized aggressive asphalt adhesive. A split release liner protects the adhesive and is removed as the underlayment is installed. This advanced system bonds to the substrate to limit damage caused by water penetration or leaks. Ultra HT is ideal for secondary water resistance.

Features

- Uniform thickness for dependable protection
- Self-seals around fasteners including nails, staples and screws
- High elongation, flexible, accommodates expansion and contraction of the substrate
- Compatible with most construction sealants & primers
- Eliminates leaks – multiple layers of protection seal out water
- Rubberized asphalt won't crack or dry out
- Aggressively adheres – sticks to plywood, metal and most other building materials for ease of application and to eliminate movement of water under the membrane
- Non-slip surface and overlap guide lines for easy installation
- Roll Size: 36"x67'

Product Specifications

Product Data

Installation Temperature Range	>50°F
Material Color	White
Roll Width	36"
Roll Length	67 ft
Carton Weight	55 lbs
Rolls per Carton	1
Area per Carton	200 ft ²
Cartons per Pallet	30
Max Temp.	250°F

Product Number

36" X 67' - 48268

Product UPC Code

7 25799 48268 3

Technical Specifications

Property	Test Method	Result
Material Thickness	ASTM D 5147	45 Mils Nom.
Flexibility @ -20°F	ASTM D 1970	Pass
Vapor Permanence	ASTM E 96	<0.02
Nail Sealability	ASTM D 1970	Pass
Tensile MD	ASTM D 1970	32 lbs/in
Tensile CMD	ASTM D 1970	35 lbs/in
Adhesion to Plywood @ 75°F	ASTM D 903/1970	>12 lbs/ft
Adhesion to Plywood @ 40°F	ASTM D 903/1970	>2 lbs/ft

*Some results listed may be the test method criteria and not actual test results.

10-YEAR LIMITED WARRANTY

MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of ten (10) years from the date of purchase when applied according to published directions.

APPROVALS

Ultra HT is tested to ASTM D 1970, Florida Building Code FL #11842.5, Miami-Dade County Approved, ICC-ES ESR 1737, Texas Department of Insurance listed, and CCMC 14048

For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit www.mfmbp.com.

