

WIND & WATER SEAL™

HIGH TEMPERATURE SEAL™



Product Highlights

Product Highlights MFM Wind & Water Seal™ is a self-adhering waterproofing underlayment composed of a non-slip polymer film laminated to a high temperature rubberized asphalt adhesive. A split release liner protects the adhesive and is removed as the underlayment is installed.

Features

- Uniform thickness for dependable protection
- Self-seals around fasteners including nails, staples & screws
- High elongation, flexible, accommodates expansion and contraction of the substrate
- Compatible with most construction sealants & primers
- Eliminates leaks – multiple layers of protection seal out water
- Rubberized asphalt won't crack or dry – protects against wind and rain
- Aggressively adheres to plywood, foam board, metal, vinyl and most other building materials for ease of application and to eliminate movement of water under the membrane
- Non-slip surface and overlap guide lines for easy installation
- Roll Size: 36"x67'

Product Specifications

Product Data

Installation Temperature Range	>50°F
Material Color	White / Gray
Roll Width	36"
Roll Length	67 ft
Carton Weight	52 lbs
Rolls per Carton	1
Area per Carton	200 ft ²
Cartons per Pallet	30
Max Temp.	250°F

Product Number

36" X 67' - 48268

Product UPC Code

7 25799 48268 3

Technical Specifications

Property	Test Method	Result
Material Thickness	ASTM D 5147	40 Mils Nom.
Flexibility @ -20°F	ASTM D 1970	Pass
Vapor Permanence	ASTM E 96	<0.01
Nail Sealability	ASTM D 1970	Pass
Adhesion to Plywood @ 75°F	ASTM D 903/1970	>12 lbs/ft
Adhesion to Plywood @ 40°F	ASTM D 903/1970	>2 lbs/ft

*Some results listed may be the test method criteria and not actual test results.

10-YEAR LIMITED WARRANTY

MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of ten (10) years from the date of purchase when applied according to published directions.

For the most current Installation Instructions, Warranties, Technical Specifications and Approvals, visit www.mfmbp.com.