

# Metal Roof Sealing Tape Master Flash®

## Features and Benefits

- Pressure activated, permanently bonding to virtually any metal roof type. Works great for repairing metal flashings, venting, gutters, skylights, copings, ductwork and more.
- The enhanced sealing solutions 100% solids formulation of synthetic resins, thermoplastics and non-curing rubber (non butyl with a built-in primer Total thickness 34 mils (+/- 2 mils)
- UV Stable Backing Available in: Black, Grey, White and Tan.
- Creates a waterproof, moisture, and airtight barrier with no additional sealing required.



	WIDTH	LENGTH
#1	2" (50mm)	50' (15m)
#2	4" (101mm)	50' (15m)
#3	6" (152mm)	50' (15m)
#4	9" (228mm)	50' (15m)

Available Colors: Black, Grey, White, Tan



## TEMPERATURE DATA

Adhesion: 20lbs+/in width

Application Temperature: 150°F to -20°F ambient

Elongation: >700% +/- 100

Low Temperature Flexibility: 1/2" radius at -30°F

Permanence: .001 perms maximum

Pliability: No cracks in membrane

Temperature Flexibility Range: -70°F – >200°F

Tensile Break PSI: 4500 PSI +/- 500 PSI

Water Proof Test: (ASTME 96B) .005 grms/100" sq./24hrs/100°F