

Mini Port Master Flash®

Features and Benefits

- Designed for small pipes, wires, antennas or solar applications on metal roofs
- Weather Protection Made of Black or Gray EPDM Rubber or High Temp Gray Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- Each Mini Port Master Flash® is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- Mini Port Master Flash® have a flexible aluminum band that will conform to any metal roof configuration.



PIPE SIZE	PORT	BASE DIAMETER	COLOR MATERIAL
Closed - 7/8" (0-22mm)	1/64 - 3/8" (1 or 9mm)	3" (76mm)	Black/Gray EPDM Red Silicone

TEMPERATURE DATA

ADVANCED OZONE RESISTANCE tested to...

EPDM 70 hour @ 500 pphm • SILICONE 70 hour @ 500 pphm

HIGH TEMPERATURE RESISTANCE tested to...

Intermittent EPDM +135°C (+275°F) • Silicone +260°C (+500°F)

Continuous EPDM +100°C (+212°F) • Silicone +225°C (+437°F)

LOW TEMPERATURE RESISTANCE tested to...

EPDM -55°C (-67°F) • Silicone -74°C (-101°F)

COMPRESSION SET Maximum... EPDM 25% • Silicone 50%