

Multi-Flash Square Vent Master Flash®

Features and Benefits

- Specially designed for square vent applications, sleeve flexibility accommodates vibration and pipe movement caused by expansion/contraction and can be used as both a standard flashing or a retrofit flashing.
- Weather Protection Made of Black EPDM Rubber or High Temp Gray Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- Each Multi Flash Square Vent Master Flash® is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- Multi-Flash Square Vent Master Flash® have a flexible aluminum band that will conform to any panel configuration and most roof pitches.



	STANDARD PIPE RANGE	RETROFIT PIPE RANGE	BASE DIAMETER	COLOR MATERIAL
#1	Closed - 5" (0-127mm)	Closed - 5" (0 - 127mm)	8" (203mm)	Black EPDM & Gray Silicone
#2	Closed - 10" (0 - 254mm)	Closed - 10" (0 - 254mm)	16-3/4" (425mm)	Black EPDM & Gray Silicone
#3	Closed - 19-1/4" (0 - 488mm)	Closed - 19-1/4" (0 - 488mm)	24-3/4" (628mm)	Black EPDM & Gray Silicone

TEMPERATURE DATA

ADVANCED OZONE RESISTANCE tested to...

EPDM 70 hour @ 500 pphm • SILICONE 70 hour @ 500 pphm

HIGH TEMPERATURE RESISTANCE tested to...

Intermittent EPDM +135°C (+275°F) • Silicone +260°C (+500°F)

Continuous EPDM +100°C (+212°F) • Silicone +225°C (+437°F)

LOW TEMPERATURE RESISTANCE tested to...

EPDM - 55°C (-67°F) • Silicone - 74°C (-101°F)

COMPRESSION SET Maximum... EPDM 25% • Silicone 50%