

Multi-Flash Master Flash®

Features and Benefits

- Designed for standard or retrofit applications for metal roofs, Two flashings in one.
- Weather Protection Made of Black or Gray EPDM Rubber or High Temp Gray Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- Each Multi-Flash Master Flash® is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- Multi-Flash Master Flash® have a flexible aluminum band that will conform to any metal roof configuration.



	STANDARD PIPE RANGE	RETROFIT PIPE RANGE	BASE DIAMETER	COLOR MATERIAL
MAXI	12" - 28-1/2" (304-723mm)	11" - 28" (279 - 711mm)	34" (863mm)	Black EPDM & Gray Silicone
#2	5/8" - 4" (15 - 101mm)	1-1/8" - 3-1/8" (28 - 79mm)	6" (152mm)	Black EPDM & Gray Silicone
#3	Closed - 5-3/4" (0 - 146mm)	2" - 5" (50 - 127mm)	8" (203mm)	Black EPDM & Gray Silicone
#4	2-3/4" - 7" (69 - 177mm)	3" - 6-1/2" (76 - 165mm)	10" (254mm)	Black EPDM & Gray Silicone
#5	4" - 8-1/4" (101 - 203mm)	3-3/4" - 7" (95 - 177mm)	11" (279mm)	Black EPDM & Gray Silicone
#6	4-3/4" - 10" (120 - 254mm)	4-1/2" - 8-1/2" (114 - 215mm)	12" (304mm)	Black EPDM & Gray Silicone
#7	6" - 11" (152 - 279mm)	5-1/4" - 10" (133 - 254mm)	14" (355mm)	Black EPDM & Gray Silicone
#8	6-3/4" - 12" (171 - 304mm)	6-1/2" - 11-3/4" (114 - 215mm)	17" (431mm)	Black EPDM & Gray Silicone
#9	9-1/2" - 20-1/2" (241 - 520mm)	9-1/4" - 20-1/2" (234 - 520mm)	25" (635mm)	Black EPDM & Gray Silicone

TEMPERATURE DATA

ADVANCED OZONE RESISTANCE tested to...

EPDM 70 hour @ 500 pphm • SILICONE 70 hour @ 500 pphm

HIGH TEMPERATURE RESISTANCE tested to...

Intermittent EPDM +135°C (+275°F) • Silicone +260°C (+500°F)

Continuous EPDM +100°C (+212°F) • Silicone +225°C (+437°F)

LOW TEMPERATURE RESISTANCE tested to...

EPDM - 55°C (-67°F) • Silicone - 74°C (-101°F)

COMPRESSION SET Maximum... EPDM 25% • Silicone 50%

