

Multi-Port Master Flash®

Features and Benefits

- Designed for standard or retrofit applications for metal roofs, Two flashings in one.
- Weather Protection Made of Black or Gray EPDM Rubber or High Temp Gray Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- Each Multi Port Master Flash® is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- Multi Port Master Flash® have a flexible aluminum band that will conform to any metal roof configuration and most roof pitches.



	STANDARD PIPE RANGE	RETROFIT PIPE RANGE	BASE DIAMETER	COLOR MATERIAL
#1	Closed - 2-3/4" (0-70mm)	1-1/4" - 2-1/4" (25 - 57mm)	4-1/2" (114mm)	Black EPDM & Gray Silicone

TEMPERATURE DATA

ADVANCED OZONE RESISTANCE tested to...

EPDM 70 hour @ 500 ppm • SILICONE 70 hour @ 500 ppm

HIGH TEMPERATURE RESISTANCE tested to...

Intermittent EPDM +135°C (+275°F) • Silicone +260°C (+500°F)

Continuous EPDM +100°C (+212°F) • Silicone +225°C (+437°F)

LOW TEMPERATURE RESISTANCE tested to...

EPDM -55°C (-67°F) • Silicone -74°C (-101°F)

COMPRESSION SET Maximum... EPDM 25% • Silicone 50%