

Solar Multi-Port MR Master Flash®

Features and Benefits

- Four ports for cable or wires per flashing to accommodate copper pipe electrical cabling.
- Weather Protection Made of Black or Gray EPDM Rubber or High Temp Gray Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- Each Master Flash® is well marked with pipe sizes, so it can be easily cut to properly conform to the pipe size used.
- Solar Multi Port MR Flash Master Flash® have a flexible aluminum band that will conform to any metal roof configuration.



	STANDARD PIPE RANGE	Port	Port	BASE DIAMETER	COLOR MATERIAL
#1	Closed - 1-15/16" (0-49mm)	1/64" - 3/8" (1-9mm)	3/16" - 15/16" (4-23mm)	4-1/2" (114mm)	Black EPDM Gray EPDM Red Silicone Gray Silicone

TEMPERATURE DATA

ADVANCED OZONE RESISTANCE tested to...

EPDM 70 hour @ 500 pphm • SILICONE 70 hour @ 500 pphm

HIGH TEMPERATURE RESISTANCE tested to...

Intermittent EPDM +135°C (+275°F) • Silicone +260°C (+500°F)

Continuous EPDM +100°C (+212°F) • Silicone +225°C (+437°F)

LOW TEMPERATURE RESISTANCE tested to...

EPDM - 55°C (-67°F) • Silicone - 74°C (-101°F)

COMPRESSION SET Maximum... EPDM 25% • Silicone 50%