

# Grade 50 Standard 22ga Color Guide

## PVDF Durapon 70<sup>®</sup> (Kynar 500<sup>®</sup> or Hylar 5000<sup>®</sup>)

(Polyvinylidene fluoride)

### STANDARD PREMIUM COLORS

(208) 745-1500

For <sup>24</sup>ga Selection, please refer to <sup>24</sup>ga Color Guide

Printed colors may vary from actual product. Metal samples available upon request. Please inquire for metal type, gauge, color, availability & lead times.








ALMOND













DARK BRONZE




HARTFORD GREEN

#### SELECT COLORS












**BRIGHT SILVER** 





NON-PAINTED







•For ENERGY STAR® Solar Reflectance data, please see panel profile brochure(s).



















PANEL SELECTION  Many more metal types, gauges, colors & widths not listed below are available.	Almond	Bone White	Bright Silver	Charcoal Gray	Dark Bronze	Dark Ivy	Deep Black	Dove Gray	Galvanized	Hartford Green	Mansard Brown	Matte Black	Regal Blue	Rustic Red	Polar White	Sherwood Green	Slate Gray	Surrey Beige	ROOFING
1/2" Corrugated Maxx™ Wall Panel	•	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•	•	•	•	Ž
1/2" Corrugated Maxx™ Roof Panel	·	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•	•	•	٠	Ы
7/8" Corrugated Maxx™ Wall Panel	·	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•	•	•	•	,
7/8" Corrugated Maxx™ Roof Panel	•	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•	•	•	•	
PBR PlusX™ Panel	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	7
Inverted R Panel SLW™	•	•	•	•	•	•	•	• (	•	•	•	• •	•	•	•	•	•	•	SIDING
7.2 PlusX** Panel	•	•		•	•		•	•	•	•	•	• •				•	•	П	•
Rapid Snop NS100™ 11.75* Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•		•	•	Ţ
Rapid Snop NS100" 15.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	ACADE
Rapid Snap NS100** 19.75** Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•		•	•	Ž
Rapid Snap NS150** 10.75** Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•	•	•	•	
Rapid Snap NS150™ 14.75" Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•	•	•	•	•
Rapid Snop NS150™ 18.75" Coverage	•	•	•	•	•	•	•	• (	• •	•	•	• •	•	•	•		•	•	Ū
Sure Snap SL100™ 12.875" Coverage	•	•	•	•	•	•	•		• •	•	•	• •	•	•	•		•	•	SO
Sure Snop SL100" 15.875" Coverage	•	•	•	•	•	•	•	• (	• •	•	•	• •	•	•	•		•	•	57
Sure Snap SL100™ 20.875" Coverage	•	•	•	•	•	•	•	• (	• •	•	•	• •	•	•	•		•	•	
Sure Snap SL150™ 10.75° Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•		•	•	Į
Sure Snop SL150™ 14.75" Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•	•	•	•	<b>A</b>
Sure Snop SL150™ 18.75" Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•			•	FRAME
Sure Snap SL175 HD™ 14" Coverage (Structural)	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•	•	•	•	•
Sure Snap SL175 HD™ 18" Coverage (Structural)	•	•	•	•	•	•	•	• (	• •	•	•	• •	•	•	•		•	•	S
Sure Lock ML100™ 12.625" Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•		•	•	9
Sure Lock ML100** 16.625** Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•	•	•	•	ij
Sure Lock ML100™ 20.625" Coverage	•	•	•	•	•	•	•	• (		•	•	• •	•	•	•			•	۲
Sure Lock ML150™ 11.75" Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•			•	
Sure Lock ML150** 15.75* Coverage	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•		•	•	Z
Sure Lock MLI50™ 19.75" Coverage	•	•	•	•	•	•	•		• •	•	•	• •	•	•	•		•	•	M
Sure Lock ML200 HD** 14.25* Coverage (Structural)	•	•	•	•	•	•	•	•	• •	•	•	• •	•	•	•			•	INTERIOR
Sure Lock ML200 HD** 18.25* Coverage (Structural)	•	•	•	•	•	•	•	•		•	•	• •		•	•		•	•	Ď
Sure Lock Seamless Batten 11°, 15° Coverage	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	AJ.
Sure Snap Seamless Batten 11°, 15°, 19° Coverage	•	•	•	•	•	•	•			•	•		•	•	•			•	ט
FlushX*** Panel 8*, 12*, 16*, 20**	•	•	•	•	•	•	•			•	•		•	•	•			•	נ
Reveal FlushX** 81,121, 161, 201 *	•	•	•	•	•	•	•			•	•		:	•	•		•	•	7
Slat Wall InfinityX'* 7°, 8°, 10°, 12°	• •	•	•	•	•	•	:			•	•		:	•	•		•	•	GUTTER
Sure Grip Board & Batten™ 4", 6", 8"	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	J





Fluropon<sup>\*</sup>

For <sup>24</sup>ga Selection, please refer to <sup>24</sup>ga Color Guide

- Standard Colors Available.
- Standard Colors available at this width at an increased cost, due to drop waste.
- Available at this width at an increased cost, due to drop waste.

\*\*Actual coverage may vary slightly due to the characteristics of the steel.
•Please inquire for metal type, gauge, color, availability and lead times.

Protective film must be removed immediately after installation.
 Please see product specification sheet for more details.

•Oil Canning is not a cause for rejection

•Profiles are not to scale.

Toll-Free: (866) 724-7171 Office: (208) 745-1500 Email: sales@briggssteel.com

Fax: (208) 745-0675

→ □ □ □ □ ↑ ▼ t □ □

4056 E 300 N Rigby, Idaho 83442

www.BriggsSteel.com



# Grade 50 Standard 24ga Color Guide

PVDF Durapon 70<sup>®</sup> (Kynar 500<sup>®</sup> or Hylar 5000<sup>®</sup>) (Polyvinylidene fluoride)

#### For 22ga Selection, please refer to 22ga Color Guide



#### SELECT COLORS



#### Low GLOSS COLORS



COPPER PENNY

### Many More Colors & Custom Colors Available





PRE-WEATHERED GALVAUME®



CHAMPAGNE













# Roofing • Siding • Facade • Post Frame • Soffit • Interior • Gutter

Panel Selection																									me®										
Many more metal types, gauges, colors & widths not listed below are available.				700				m								9	ıze ıs		_ (	_	phite	-	0		Patina Green Pre-Weathered Galvalume			La C							
	opper	F	ay	Award Dilue Blued Gunmetal	Vhite	White	oly 10	Burnished Slate Champagne	Charcoal Grav	ape	Classic Green	al Red	Copper Penny Dark Bronze		Slack	Blue	Extra Dark Bronze Galvalume® Plus	jzed	Hartford Green	Hemilock Green Lead Coat	Legendary Graphite	Mansard Brown	Medium Bronze	t Gray	Green	Jed Jed	3lue	Sandstone Sherwood Green	Tan		lue irav	White	otta	Tropical Patina	ered Zinc
	AgedCopper	Almond	AshGray	Blued (	Bone White	Bright White	Burgundy	Burnished Sig Champagne	Charce	Cityscape	Classic	Colonial Red	Copper Peni	Dark Iv	Deep Black	Electric Blue	Galval	Galvanized	Hartfor	LeadCoat	Legenc	Mansa	Medium Bro	Musket Gray	Patina Green Pre-Weather	RegalRed	Royal Blue	Sandstone	Sierra Tan	Silver	Slate Blue	Stone White	Teal Terra Cotta	Tropica	Weathe
PBR PlusX™ Panel	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	• •	•	•	• •	•	• •	•	•
Inverted R Panel SLW™	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •		•
7.2 PlusX™ Panel	•	•	•		•	•	•	•	•	•	•	•	• •		•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	• •	•	• •	,	•
Rapid Snap NS100™11.75*Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	• •	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	, •	•
Rapid Snap NS100™ 15.75* Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Rapid Snap NS100™ 19.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Rapid Snap NS150™10.75*Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Rapid Snap NS150™14.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Rapid Snap NS150™18.75° Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL100™ 12.875" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL100™ 16.875" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL100™ 20.875" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL150™ 10.75* Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL150™ 14.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL150™ 18.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL175 HD™ 14* Coverage (Structural)	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Snap SL175 HD™ 18" Coverage (Structural)	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	• •	•	•	• •	•	• •		•
Sure Lock ML100™ 12.625" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •		•
Sure Lock ML100™ 16.625" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Lock ML100™ 20.625" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •		•
Sure Lock ML150™11.75" Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Lock ML150 <sup>th</sup> 15.75° Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Lock ML150 <sup>th</sup> 19.75° Coverage	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •		•
Sure Lock ML200 HD™ 14.25* Coverage (Structural)	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	• •	•	• •	•	•
Sure Lock ML200 HD™ 18.25* Coverage (Structural)	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•		•	•	•	• •	•	•	•	•	•	• •	•	• •		•
Sure Lock Seamless Batten 11", 15" Coverage	•	•	•	:	•	•	•			•	•	•	:	•	•	•	:	•	•	•	•	•		•	•	•	•		•	•	•	:	•	•	•
Sure Snap Seamless Batten 11", 15", 19" Coverage	•	•	•	*	•	•	•			•	•	•	:	•	•	•	:	•	•	:	• • *	•		•	•	•	•		•	•		:	•	•	•
FlushX** Panel 8", 12", 16", 20"	•	•	•	*	•	•	•	•		•	•	•	•	•	•	•		•	•	•	• • *		•	•	•	•	•		•	•		:	•	•	•
Reveal FlushX**8*,12*, 16*, 20*	•	•	•	*	•	•	•			•	•	•	•	•	•	•	•	•	•	•	• • *	•	•	•	•	:	•		•	•	•		•	•	•
Slat Wall InfinityX'* 7", 8", 10", 12"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•		•	•	•	•	•	•	•
Sure Grip Board & Batten™8"	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	•	•	• •		•
5° & 6 K-Style InfinityX™	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•	•
							_																		Þ	wail	able	e wit	h	_					

- Standard colors available at this width at an increased cost, due to drop waste.
- Components available with alternate pricing and longer lead times.
- \* Not available in this width.
- Available at this width at an increased cost, due to drop waste.

WE OFFER MANY COLORS & PROFILES NOT INCLUDED ON THIS CHART For 22ga Selection, please refer to 22ga Color Guide **Condensation Control** for Metal Buildings

\*\*Actual coverage may vary slightly due to the characteristics of the steel.

"Actual coverage may vary singing use to the characteristics or needs. Please inquire for metal type, gauge, color, availability and lead times. Protective film must be removed immediately after installation. Please see product specification sheet for more details. Oil Canning is not a cause for rejection. Profiles are not to scale.

Toll-Free: (866) 724-7171 Office: (208) 745-1500 Email: sales@briggssteel.com

www.BriggsSteel.com 4056 E 300 N - Rigby, Idaho 83442





# Grade 50 Standard 26ga Color Guide

(208) 745-1500

### Ceranamel XT-40S™ High Performance SMP

(silicone modified polyester)

### STANDARD COLORS





Many More Colors & Custom Colors Available



#### NON-PAINTED

SLATE BLUE







COPPER PENNY\*

•For ENERGY STAR® Solar Reflectance data, please see panel profile brochure(s).













PANEL SELECTION  Many more metal types, gauges, colors & widths not listed below are availa	ıble.	Almond	Antique Ivory	Ash Gray	Bone White	Burnished Slate	Charcoal Gray	Classic Green	Copper Penny	Dark Bronze	Deep Black	Galvanized	Hartford Green	Mansard Brown	Matte Black	Musket Grav	Pebble Clay	Sierra Tan	Slate Blue	Slate Gray Terra Cotta	ROOFING
Tuff Rib PlusX™ Ponel	_>	•	•	•	• •	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	• •	្រ
1/2" Corrugated Maxx" Wall Panel	~~	•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	Ġ
1/2" Corrugated Maxx™ Roof Panel	~~	•	•	•	• •	•	•	•	•	•	• (	•	•	•	• •	•	•	•	•	• •	Ö
7/8" Corrugated Maxx" Wall Panel	$\sim$	•	•	•	• •	•	•	• •	•	•	•	•	•	•	• •	•	•	•	•	• •	SIDING
7/8" Corrugated Maxx™ Roof Panel	$\sim$	•	•	•	• •	•	•	• •	•	•	•	•	•	•	• •	•	•	•	•	• •	
PBR PlusX** Panel	$\wedge$	•	•	•	• •	•	•	• •	•	•	• (	•	٠	•	• •	•	•	•	•	• •	Ä
Inverted R Ponel SLW™	$\checkmark$	•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	FACADE
Rapid Snap NS100™ 11.75" Coverage		•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	
Rapid Snap NS100™ 15.75" Coverage		•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	
Rapid Snap NS100™ 19.75° Coverage		•	•	•	• •	•	•	•	•	•	• (	•	•	•	• •	•	•	•	•	• •	ď
Sure Snap SL100™ 12.875° Coverage		•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	POST
Sure Snap SL100™ 16.875" Coverage		•	•	•	• •	•	•	• •	•	•	• •	•	•	•	• •	•	•	•	•	• •	Ĭ
Sure Snap SL100™ 20.875" Coverage		•	•	•	• •	•	•	•	•	•	• (	•	•	•	• •	•	•	•	•	• •	🖔
Sure Lock ML100™ 12.525" Coverage	$\Box$	•	•	•	• •	•	•	• •	•	•	• •	•	•	•	• •	•	•	•	•	• •	FRAME
Sure Lock ML100™ 16.625* Coverage	$\Box$	•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	
Sure Lock ML100™ 20.625° Coverage	$\Box$	•	•	•	• •	•	•	• •	•	•	• (	•	•	•	• •	•	•	•	•	• •	
Sure Lock ML150™ 11.75* Coverage		•	•	•	• •	•	•	•	•	٠	•	•	•	•	• •	•	•	•	•	• •	SOFFIT
Sure Lock ML150™ 15.75" Coverage		•	•	•	• •	•	•	• •	•	•	• •	•	•	•	• •	•	•	•	•	• •	7
Sure Lock ML150™ 19.75" Coverage		•	•	•	• •	•	•	• •	•	•	• •	•	•	•	• •	•	•	•	•	• •	Ž
Sure Lock Seamless Batten 11", 15" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	INTERIOR
Sure Snap Seamless Batten 11", 15", 19" Coverage		•	•	•	•	•	•	•	•	•	• (	•	•	•	•	•	•	•	•	•	Ž
FlushX" Panel 8", 12", 16", 20"	7	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	אל
Reveal FlushX <sup>™</sup> 8",12", 16", 20"	7	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Slat Wall InfinityX" 7, 87, 10, 12"	7	•		•	•	•	•	•	•	•	•	•	•	•	• •	•	•	•	•	•	GUTTER
Sure Grip Board & Batten** 4*, 6*, 8*		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	] 7
5" & 6 K-Style InfinityX™	7	•	•	•	•	•	•	• •	•	•	• •	•	•	•	• •	•	•	•	•	•	

- Standard Colors Available.
- Standard Colors available at this width at an increased cost, due to drop waste.
- Available at this width at an increased cost, due to drop waste.
- Components available with alternate pricing and longer lead times.

Ceranamel XT-405





- $\boldsymbol{\cdot}$  Many other panel profiles are available. Please talk to representative for details.
- · Standard & Custom trim available for all profiles and for profiles not listed.
- Custom trim options available for a variety of different applications.
- · Large Inventory of Coil, Flat Sheet, Fasteners, Sealants & Accessories.



Email: sales@briggssteel.com Fax: (208) 745-0675

() ⊙ ⊙ () h y t □ □

www.BriggsSteel.com

4056 E 300 N Rigby, Idaho 83442













\*\*Actual coverage may vary slightly due to the characteristics of the steel.

•Please inquire for metal type, gauge, color, availability and lead times. ·Protective film must be removed immediately after installation.

Please see product specification sheet for more details.

•Oil Canning is not a cause for rejection. •Profiles are not to scale.