



Grade 50 Standard 24ga Color Guide

(208) 745-1500

PVDF Durapon 70® (Kynar 500® or Hylar 5000®)
(Polyvinylidene fluoride)

STANDARD PREMIUM COLORS

For 22ga Selection please refer to 22ga Color Guide

Printed colors may vary from actual product. Metal samples available upon request. Please inquire for metal type, gauge, color, availability & lead times.

STONE WHITE	BONE WHITE	BRIGHT WHITE	ALMOND	SANDSTONE	SIERRA TAN
SLATE GRAY	MUSKET GRAY	ASH GRAY	CITYSCAPE	CHARCOAL GRAY	DEEP BLACK
MATTE BLACK	MANSARD BROWN	MEDIUM BRONZE	DARK BRONZE	EXTRA DARK BRONZE	BURNISHED SLATE
BURGUNDY	REGAL RED	COLONIAL RED	TERRA COTTA	HARTFORD GREEN	CLASSIC GREEN
				ECONOMY 	
HEMLOCK GREEN	TEAL	SLATE BLUE	ROYAL BLUE		

SELECT COLORS

DARK IVY	PATINA GREEN	SHERWOOD GREEN	TROPICAL PATINA	AWARD BLUE	ELECTRIC BLUE
AGED COPPER	SILVER	LEAD COAT	WEATHERED ZINC	BLUED GUNMETAL	LEGENDARY GRAPHITE (low glaze)
PRE-WEATHERED GALVALUME®	CHAMPAGNE	COPPER PENNY			

LOW GLOSS COLORS

BURNISHED SLATE	CHARCOAL GRAY	DARK BRONZE	DEEP BLACK	SLATE GRAY

Many More Colors & Custom Colors Available



*Steel Substrate Grade D (yield strength of 50,000 psi) & Grade E (yield strength of 80,000 psi)
 *Substrate Coatings - Galvalume® AZ50, AZ55, AZ60, AZ70 & Galvanized G40, G60, G90, G100.
 *Protective film must be removed immediately after installation.
 *Due to product advancements, changes and other factors, we reserve the right to modify or delete the information herein without prior notice.
 *Galvalume® is a registered trademark of BIEC International, Inc.
 *Durapon 70® is a registered trademark of Dura Coat Products, Inc.
 *Dura Coat® is a registered trademark of Dura Coat Products, Inc.
 *Teflon® is a registered trademark of The Chemours Company FC, LLC.
 *Fluropon® is a trademark of The Sherwin-Williams Company.
 *Kynar 500® is a registered trademark of Arkema, Inc.
 *Hylar 5000® is a registered trademark of Solvay Solexis, Inc.
 *Sherwin-Williams® is a registered trademark of The Sherwin-Williams Company.
 *Metallic are batch sensitive & therefore variations are very common and expected to vary.
 **Not all products listed offer 35 year paint warranty and warranties vary.
 ***Not all products listed offer 40 year warranty and warranties vary.
 *Oil Canning is not a cause for rejection. See oil canning disclaimer.

(208) 745-1500

Ceranamel XT-40S™ High Performance SMP
(silicone modified polyester)

STANDARD COLORS



Printed colors may vary from actual product. Metal samples available upon request. Please inquire for metal type, gauge, color, availability & lead times.

				
BONE WHITE	ALMOND	ANTIQUE IVORY	ASH GRAY	SIERRA TAN
				
SLATE GRAY	MUSKET GRAY	PEBBLE CLAY	CHARCOAL GRAY	DEEP BLACK
				
MATTE BLACK	MANSARD BROWN	MEDIUM BRONZE	DARK BRONZE	BURNISHED SLATE
				
BURGUNDY	COLONIAL RED	TERRA COTTA	HARTFORD GREEN	CLASSIC GREEN
				
SLATE BLUE	COPPER PENNY*			

Many More Colors & Custom Colors Available



NON-PAINTED

	
GALVALUME® PLUS (acrylic coated)	GALVANIZED

*For ENERGY STAR® Solar Reflectance data, please see panel profile brochure(s).



Dura Coat
PRODUCTS
An Axalta Coating Systems Company

Ceranamel XT-40S™

Up to a
30
YEAR
Paint Warranty

-Steel Substrate Grade D (yield strength of 50,000 psi) & Grade E (yield strength of 80,000 psi).
-Substrate Coatings - Galvalume® AZ50, AZ55, AZ60, AZ70 & Galvanized G40, G60, G90, G100.
-Due to product advancements, changes and other factors, we reserve the right to modify or delete the information herein without prior notice.

-Dura Coat is a registered trademark of Dura Coat Products, Inc.
-Ceranamel XT-40S is a trademark of Dura Coat Products, Inc.
-Galvalume® is a registered trademark of BIEC International, Inc.
-Protective film must be removed immediately after installation.

-ENERGY STAR® and the ENERGY STAR® mark are registered trademarks owned by the U.S. Environmental Protection Agency.
*Metallics are a premium cost and are batch sensitive, therefore variations are very common and expected.

-For ENERGY STAR® Solar Reflectance data, please inquire for more information.
-Not all products listed offer 30 year paint warranty and warranties vary.
-Not all products qualify for ENERGY STAR® rating.
-Oil Canning is not a cause for rejection. See oil canning disclaimer.

PANEL SELECTION		Almond	Antique Ivory	Ash Gray	Bone White	Burgundy	Burnished Slate	Charcoal Gray	Classic Green	Colonial Red	Copper Penny	Dark Bronze	Deep Black	Galvalume®	Galvanized	Hartford Green	Mansard Brown	Matte Black	Medium Bronze	Musket Gray	Pebble Clay	Sierra Tan	Slate Blue	Slate Gray	Terra Cotta
Many more metal types, gauges, colors & widths not listed below are available.																									
Tuff Rib PlusX™ Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1/2" Corrugated Maxx™ Wall Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1/2" Corrugated Maxx™ Roof Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
7/8" Corrugated Maxx™ Wall Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
7/8" Corrugated Maxx™ Roof Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
PBR PlusX™ Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Inverted R Panel SLW™		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 11.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 15.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 19.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 12.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 16.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 20.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 12.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 16.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 20.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 11.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 15.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 19.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock Seamless Batten 11", 15" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap Seamless Batten 11", 15", 19" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
FlushX™ Panel 8", 12", 16", 20"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Reveal FlushX™ 8", 12", 16", 20"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Slot Wall InfinityX™ 7", 8", 10", 12"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Grip Board & Batten™ 4", 6", 8"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
5" & 6 K-Style InfinityX™		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

- Standard Colors Available.
- Standard Colors available at this width at an increased cost, due to drop waste.
- Available at this width at an increased cost, due to drop waste.
- Components available with alternate pricing and longer lead times.

Ceranamel XT-405™

Dura Coat
PRODUCTS
An Axalta Coating Systems Company

WE OFFER MANY COLORS & PROFILES NOT INCLUDED ON THIS CHART

- Many other panel profiles are available. Please talk to representative for details.
- Standard & Custom trim available for all profiles and for profiles not listed.
- Custom trim options available for a variety of different applications.
- Large Inventory of Coil, Flat Sheet, Fasteners, Sealants & Accessories.

**Actual coverage may vary slightly due to the characteristics of the steel.
 •Please inquire for metal type, gauge, color, availability and lead times.
 •Protective film must be removed immediately after installation.
 •Please see product specification sheet for more details.
 •Oil Canning is not a cause for rejection.
 •Profiles are not to scale.

Toll-Free: (866) 724-7171
 Office: (208) 745-1500
 Email: sales@briggssteel.com
 Fax: (208) 745-0675

www.BriggsSteel.com
 4056 E 300 N
 Rigby, Idaho 83442




(208) 745-1500

PVDF Durapon 70® (Kynar 500® or Hylar 5000®)
(Polyvinylidene fluoride)


For 24ga Selection: please refer to 24ga Color Guide

STANDARD PREMIUM COLORS


Printed colors may vary from actual product. Metal samples available upon request. Please inquire for metal type, gauge, color, availability & lead times.



BONE WHITE



ALMOND



SANDSTONE




SLATE GRAY




CHARCOAL GRAY




DEEP BLACK



MATTE BLACK



MANSARD BROWN



MEDIUM BRONZE



DARK BRONZE




HARTFORD GREEN

Many More Colors & Custom Colors Available



SELECT COLORS



POLAR WHITE



DOVE GRAY



SURREY BEIGE



RUSTIC RED



SHERWOOD GREEN



DARK IVY



REGAL BLUE



BRIGHT SILVER

NON-PAINTED



GALVALUME® PLUS (acrylic coated)



GALVANIZED

-For ENERGY STAR® Solar Reflectance data, please see panel profile brochure(s).



-Steel Substrate Grade D (yield strength of 50,000 psi) & Grade E (yield strength of 80,000 psi)
 -Substrate Coatings - Galvalume® AZ50, AZ55, AZ60, AZ70 & Galvanized G40, G60, G90, G100.
 -Protective film must be removed immediately after installation.
 -Due to product advancements, changes and other factors, we reserve the right to modify or delete the information herein without prior notice.
 -Galvalume® is a registered trademark of BIEC International, Inc.

-Durapon 70® is a registered trademark of Dura Coat Products, Inc.
 -Dura Coat® is a registered trademark of Dura Coat Products, Inc.
 -Teflon® is a registered trademark of The Chemours Company FC, LLC.
 -Fluropon® is a trademark of The Sherwin-Williams Company.
 -Kynar 500® is a registered trademark of Arkelma, Inc.
 -Hylar 5000® is a registered trademark of Solvay Solexis, Inc.

-Sherwin-Williams® is a registered trademark of The Sherwin-Williams Company.
 -ENERGY STAR® and the ENERGY STAR® mark are registered trademarks owned by the U.S. Environmental Protection Agency.
 *Metallics are batch sensitive & therefore variations are very common and expected to vary.

-For ENERGY STAR® Solar Reflectance data, please inquire for more information.
 -Not all products listed offer 35 year paint warranty and warranties vary.
 -Not all products qualify for ENERGY STAR® rating.
 **Not all products listed offer 40 year warranty and warranties vary.
 -Oil Canning is not a cause for rejection. See oil canning disclaimer.

PANEL SELECTION		Almond	Bone White	Bright Silver	Charcoal Gray	Dark Bronze	Dark Ivy	Deep Black	Dove Gray	Galvalume®	Galvanized	Hartford Green	Mansard Brown	Matte Black	Medium Bronze	Regal Blue	Rustic Red	Polar White	Sandstone	Sherwood Green	Slate Gray	Surrey Beige	
1/2" Corrugated Maxx™ Wall Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1/2" Corrugated Maxx™ Roof Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
7/8" Corrugated Maxx™ Wall Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
7/8" Corrugated Maxx™ Roof Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
PBR PlusX™ Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Inverted R Panel SLW™		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
7.2 PlusX™ Panel		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 11.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 15.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS100™ 19.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS150™ 10.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS150™ 14.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Rapid Snap NS150™ 18.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 12.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 16.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL100™ 20.875" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL150™ 10.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL150™ 14.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL150™ 18.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL175 HD™ 14" Coverage (Structural)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap SL175 HD™ 18" Coverage (Structural)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 12.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 16.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML100™ 20.625" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 11.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 15.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML150™ 19.75" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML200 HD™ 14.25" Coverage (Structural)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock ML200 HD™ 18.25" Coverage (Structural)		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Lock Seamless Batten 11", 15" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Snap Seamless Batten 11", 15", 19" Coverage		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
FlushX™ Panel 8", 12", 16", 20"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Reveal FlushX™ 8", 12", 16", 20"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Slot Wall InfinityX™ 7", 8", 10", 12"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sure Grip Board & Batten™ 4", 6", 8"		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

ROOFING • SIDING • FACADE • POST FRAME • SOFFIT • INTERIOR • GUTTER



SHERWIN-WILLIAMS
Call Coatings

Fluorpon™

For 24ga Selection please refer to 24ga Color Guide

- Standard Colors Available.
- Standard Colors available at this width at an increased cost, due to drop waste.
- Available at this width at an increased cost, due to drop waste.

**Actual coverage may vary slightly due to the characteristics of the steel.
•Please inquire for metal type, gauge, color, availability and lead times.
•Protective film must be removed immediately after installation.
•Please see product specification sheet for more details.
•Oil Canning is not a cause for rejection.
•Profiles are not to scale.

Toll-Free: (866) 724-7171
Office: (208) 745-1500
Email: sales@briggssteel.com
Fax: (208) 745-0675



Copyright © 2020 by Briggs Steel. All rights reserved. Rev 05/20.

Due to product advancements, changes and other factors, we reserve the right to modify or delete the information herein without prior notice.

www.BriggsSteel.com

4056 E 300 N

Rigby, Idaho 83442





(208) 745-1500

Grade 50 • 24ga Low Gloss

Kynar 4x10 Sheet

Printed colors may vary from actual product. Metal samples available upon request. Please inquire for metal type, gauge, color, availability & lead times.



DEEP BLACK



CHARCOAL GRAY



DARK BRONZE



BURNISHED SLATE



SLATE GRAY

-For ENERGY STAR® Solar Reflectance data, please see panel profile brochure(s).



-Steel Substrate Grade D (yield strength of 50,000 psi) & Grade E (yield strength of 80,000 psi)
-Substrate Coatings - Galvalume® AZ50, AZ25, AZ60, AZ70 & Galvanized G40, G60, G90, G100.
-Protective film must be removed immediately after installation.
-Due to product advancements, changes and other factors, we reserve the right to modify or delete the information herein without prior notice.
-Galvalume® is a registered trademark of BIEC International, Inc.

-Durapon 70® is a registered trademark of Dura Coat Products, Inc.
-Dura Coat® is a registered trademark of Dura Coat Products, Inc.
-Teflon® is a registered trademark of The Chemours Company FC, LLC.
-Fluropon® is a trademark of The Sherwin-Williams Company.
-Kynar 500® is a registered trademark of Arkema, Inc.
-Hylar 5000® is a registered trademark of Solvay Solexis, Inc.

-Sherwin-Williams® is a registered trademark of The Sherwin-Williams Company.
-ENERGY STAR® and the ENERGY STAR® mark are registered trademarks owned by the U.S. Environmental Protection Agency.
*Metallics are batch sensitive & therefore variations are very common and expected to vary.

-For ENERGY STAR® Solar Reflectance data, please inquire for more information.
-Not all products listed offer 35 year paint warranty and warranties vary.
-Not all products qualify for ENERGY STAR® rating.
**Not all products listed offer 40 year warranty and warranties vary.
-Oil Canning is not a cause for rejection. See oil canning disclaimer.

