



KasselShake Oxford Copper Shingle will add beauty and protection to your home. Copper Shingles deep grooves gives the appearance of random hand split wood shake through a precision stamping formation. It will fit in any neighborhood and have lasting curb appeal and home value.

Oxford Copper Shingles are long lasting and use a four way interlocking system to lock each panel to eachother and secured to the roof through five nail clips that are attached to the panel locks to allow expansion and contraction.

Product Specifications

Exposure Height:	12"	<p>Additional Materials: Other materials available include silicone sealant, copper hold-down clips, pipe flashings, and corrosion resistant fasteners</p> <p>Underlayment: Per manufacturer roof must be covered with at least one layer of 30 lb. felt underlayment or equivalent.</p> <p>Dissimilar Materials: Copper material should not be installed in contact with dissimilar metals, concrete, stucco, asbestos, siding, masonry, or other corrosive nonmetallic materials that might be continually wet.</p> <p>Dissimilar materials should be painted or otherwise protected when they are in contact with copper. Divert drainage from copper roofing away from other materials. To prevent wood damage, use pressure treated wood.</p>
Exposure Width:	60"	
Weight/Square:	95 lbs	
Material:	Copper Sheet	
Panel Uses:	Residential & Light Commercial Roofs & Mansards	
Material Hardness:	HFR 82.0	
Yield Strength:	40.1 ksi	
Tensile Strength:	41.1 ksi	
Finish:	Mill Finish Copper will Patina	
Pitch:	3:12 or greater pitch	