

304 Stainless Steel 2b

Product Highlights

304 stainless steel with a 2B finish is a versatile and widely used material that offers good corrosion resistance and a smooth, bright surface finish. The 2B finish is produced by cold rolling and annealing the steel without applying a surface finish, resulting in a slightly reflective appearance. This makes it suitable for a wide range of applications for architectural trim and general industrial use. While it may not have the decorative appeal of some other finishes, the 2B finish provides a practical and economical solution for projects where a highly reflective surface is not required.



Product Specifications

Applications:	Residential, Commercial, Agriculture, Wall	Fire Resistant:	Class A Severe Fire Test Exposure
Thickness:	22, 24, 26 Gauge	Yield Strength:	Min. (ksi) 30 ASTM A240
Substrate:	Galvanized	Hardness:	Max. (Rb) 92 ASTM A240
Coating:	G90 Coating	Tensile Strength:	Min. (ksi) 75 ASTM A240
Length:	120'	Thermal Conductivity:	9.4F° Btu/ft. hr
Width:	48' Standard	Field Conditions:	Oil Canning is inherent in all light gauge metal products & is not a cause for rejection. Visit www.briggssteel.com/oil-canning for more information.
		Accessories:	Trim, Custom Trim, Fasteners, Sealant, Closures, Venting, Pipe Flashings, Underlayment, Snow Retention, Polycarbonate Panels, Many Tools.
		More Details:	For more information about this material, please visit www.BriggsSteel.com/304-stainless-steel
		Special Consideration:	<ul style="list-style-type: none"> • Batch Sensitive • Must be installed immediately • Maintenance required

Note: For standard color selection, consult the current Briggs Steel Color Selection Guides. Custom colors are available upon request.
 **Actual coverage may vary slightly due to the characteristics of the steel.
 Patent Number US 10,336,114,B2

•Steelscape® is a registered trademark of Steelscape, LLC.
 •Rustic Rawhide® is a registered trademark of Steelscape, LLC.
 •TruZinc® is a registered trademark of Steelscape, LLC.